

Outdoor AC Automatic Voltage Stabilisers & Regulators

Cost Efficient Voltage Stabilisation Solutions with Fast Speed of Response and High Output Voltage Accuracy

AC mains voltage fluctuations can cause equipment to behave erratically and malfunction. Some systems may even break down due to these fluctuations, noise or spikes. Failure to ensure the incoming mains voltage is stable and clean, can often result in costly equipment repairs.

Ashley-Edison, Electromechanical / Electronic Servo **OSES Series** Outdoor AC Automatic Voltage Stabilisers, are designed to ensure that, should the incoming mains voltage drift high or low, the output voltage remains continuously constant. Characterised by high efficiency, they are completely unaffected by Power Factor, Load and Frequency variations. They are capable of withstanding high instantaneous overloads and do not generate any magnetic interference. Compact in size, quiet in operation, these Voltage Stabilisers are suitable for indoor and outdoor use and may be located near to sensitive equipment.

Our Voltage Stabilisers are equipped with **Bypass Control Switches**. These switches can be activated when required.

Soft Switch-ON feature will ensure that the Voltage Stabiliser is at its minimum upon switch-on before it commences full stabilization. Lack of this feature may cause a high output voltage surge from the stabiliser.

OSES SERIES SINGLE PHASE 3KVA ~ 100KVA



Models:

High Voltage (H) Models
220V; 230V or 240V
(Single Phase)

Low Voltage (L) Models
115V; 120V or 127V
(Single Phase)

Features:

- **Wide Range of Voltage Stabiliser**
Single Phase Up to 100KVA
- **Input Swing Range**
Input Swing Range Available from $\pm 15\%$, $\pm 20\%$, $\pm 25\%$, $\pm 30\%$, $\pm 35\%$,
(To Specify)
- **Output Voltage Regulation**
Output Voltage Accuracy $\pm 1\%$,
- **High Efficiency**
Better than 98%
- **Standard Protection Features**
Input circuit breaker
Voltmeter (Internal)
Bypass control switch
- **Optional Accessories**
Output circuit breaker
Ammeter (Internal)
Bypass control switch
Over Low Voltage Protection
Heater / Thermostat for Low
Temperature Applications
Manual maintenance bypass switch

- **Compliance with International Standards**
BS EN50081-1;2/IEC 61000-4-3;4
BS EN5490/IEC 60529
- **CE Conformity**
EN55022, EN50082-2, ENV50140-1
- **Warranty**
2 Years

Applications

- Communication Systems
- TV/Radio Broadcasting Stations
- Security Systems
- Communication Stations
- Lighting Systems
- Golf Course Lighting Systems
- Perimeter Lighting



Outdoor AC Automatic Voltage Stabilisers & Regulators

Technical Specifications

Input Swing Range	±15%, ±20%, ±25%, ±30%, ±35%, Single Phase
Output Voltage	Pre-settable for any voltage between 220V; 230V or 240V
Output Voltage Accuracy	± 1%
Frequency	47 – 65 Hz
Response Time	<1.5ms
Correction Time	A 10% supply variation will be corrected to within 2.5% in 0.6 seconds
Efficiency	98%
Power Factor	Any lagging to 0.95 leading
Surge ratings	10 x max current rating for 2 seconds 3 x max current rating for 1 minutes 2 x max current rating for 5 minutes
Surge Suppression	Protect loads against high-energy spikes and transient voltage.
Surge Arrester	40KA at 275V AC Class III (IEC 61643-1:1998-02, EN 61643-11:2001)

Total Harmonic Distortion	<1%
Soft Switch-ON	Ensure that the output voltage is at its minimum upon Switch-On before it commence full stabilization
Environment	Temperature range –15 to 50 °C. Derate by 2% for each additional °C Up to max 65 °C . Suitable for indoor tropical use 95% RH (non-condensing). Maximum altitude 1000m. Derate by 2.5% for each additional 500m
Construction	Enclosures to IP54, BS EN5490 / IEC 60529
EMC Conformance	BS EN50081-1;2 / IEC 61000-4-3;4
CE Conformity	EN55022, EN50082-2, ENV50140-1
Standard Features	Input circuit breaker Bypass control switch internal voltmeter
Optional Accessories	Output circuit breaker Over/Low voltage protection Ammeter Heater / Thermostat for Low Temperature Applications Manual maintenance bypass switch
Warranty	2 Years

Note: Optional accessories added may affect dimension, subject to confirmation.

Note: 1) Special voltage configurations available to order
2) Higher KVA rating options available to order

Single Phase Model: OSES-H-S*

Model:	Rating KVA	Amps @ 220V	Amps @ 230V	Amps @ 240V	Dimensions (mm) W x H x D	Weight (Kgs)
OSES 3H-S	3	13.6	13	12.5	Dimensions and Weight upon request	
OSES 5H-S	5	23	22	21		
OSES 8H-S	8	36	35	33		
OSES 10H-S	10	45	44	42		
OSES 15H-S	15	68	65	63		
OSES 20H-S	20	91	87	83		
OSES 25H-S	25	113	108	104		
OSES 30H-S	30	136	130	125		
OSES 40H-S	40	182	174	167		
OSES 50H-S	50	227	217	208		
OSES 60H-S	60	273	261	250		
OSES 75H-S	75	341	326	313		
OSES 100H-S	100	455	435	417		

Copyright © 2009 Ashley-Edison reserve the right to change any or all of the specifications indicated or Implied without prior notice.



CE

